

## AD200 AGRI-DRYER

**kW:** 18kW  
**Remote Access Connection Avail.:** Yes  
**Length (mm):** 2900  
**Height (mm):** 2500  
**Width (mm):** 1200  
**Control Panel (mm):** 400  
**Plug Connection Included:** Yes

**Structure:** Insulated structure, doors and ceiling: Polystyrene insulation sandwiched between white CHROMADEK® (0.6mm) faceplate both sides, one entrance

**Airflow:** Galvanised cased axial fans with high-speed Class H 3 phase (380v) motors and aluminium impeller and blades

**Heating:** 6 x 3kW Electric elements mounted to a treated mild steel bank

**Trays:** 40  
**Tray Area (m<sup>2</sup>):** 21,6  
**Installation Required:** Optional Extra  
**Assembly Required:** Pre-assembled  
**Weight:** 450kgs  
**Manual:** Included  
**Training Material:** Included  
**No. Fans:** 2  
**No. Elements:** 6  
**Portable / On Wheels:** Optional Extra  
**Electrical panel:** Equipped with isolator, circuit breakers, fan contactor and overload, heater contactor, overheat safety thermostat, over/under voltage monitor, emergency stop, PLC with pre-loaded software, temperature and humidity sensor, digital timer, UPS, inlet and exhaust damper  
**Conversions Available:**  
Electric, Solar, Generator, Gas, Hot Water

