

## AD2500 AGRI-DRYER

**kW:** 96kW

**Remote Access Connection Avail.:** Yes

**Length (mm):** 6000

**Height (mm):** 2800

**Width (mm):** 3000

**Control Panel (mm):** 400

**Plug Connection Included:** No

**Structure:** Insulated structure, doors and ceiling: Polystyrene insulation sandwiched between white CHROMADEK® (0.6mm) faceplate both sides, one entrance

**Airflow:** Galvanised cased axial fans with high-speed Class H 3 phase (380v) motors and aluminium impeller and blades

**Heating:** 32 x 3kW Electric elements mounted to a treated mild steel bank

**Trays:** 500

**Tray Area (m<sup>2</sup>):** 270

**Installation Required:** Yes

**Assembly Required:** Assembled On Site

**Weight:** 3750kgs

**Manual:** Included

**Training Material:** Included

**No. Fans:** 3

**No. Elements:** 32

**Portable / On Wheels:** No

**Electrical panel:** Equipped with isolator, circuit breakers, fan contactor and overload, heater contactor, overheat safety thermostat, over/under voltage monitor, emergency stop, PLC with pre-loaded software, temperature and humidity sensor, digital timer, UPS, inlet and exhaust damper

**Conversions Available:**

Electric, Solar, Gas, Hot Water, Turbine

