

## AD4500 AGRI-DRYER

**kW:** 144kW  
**Remote Access Connection Avail.:** Yes  
**Length (mm):** TBA  
**Height (mm):** TBA  
**Width (mm):** TBA  
**Control Panel (mm):** 400  
**Plug Connection Included:** No

**Structure:** Insulated structure, doors and ceiling:  
Polystyrene insulation sandwiched between white  
CHROMADEK® (0.6mm) faceplate both sides, one  
entrance

**Airflow:** Galvanised cased axial fans with high-  
speed Class H 3 phase (380v) motors and  
aluminium impeller and blades

**Heating:** 48 x 3kW Electric elements mounted to a  
treated mild steel bank

**Trays:** 900  
**Tray Area (m<sup>2</sup>):** 486  
**Installation Required:** Yes  
**Assembly Required:** Assembled On Site  
**Weight:** 4000kgs  
**Manual:** Included  
**Training Material:** Included  
**No. Fans:** 5  
**No. Elements:** 48  
**Portable / On Wheels:** No  
**Electrical panel:** Equipped with isolator, circuit  
breakers, fan contactor and overload, heater  
contactor, overheat safety thermostat,  
over/under voltage monitor, emergency stop,  
PLC with pre-loaded software, temperature and  
humidity sensor, digital timer, UPS, inlet and  
exhaust damper  
**Conversions Available:**  
Electric, Solar, Gas, Hot Water, Turbine

