



# CD1500 Container Dryer Type 2 Hot Water Boiler

## Most common crops are:

Banana, mango, peach, fig, apple, pineapple, tomato, berries, chillies, paprika, garlic, onion, cassava, herbs, spices, vegetables, flowers, nuts, curing of meat & fish.

## Specifications

Model	CD1500
kW	*5kW/**20
Trays	240
Tray Area (m <sup>2</sup> )	129.6
Wet Product In (kg)	1200-1800
Est. Dried Product Out (kg)	240-590
Length (mm)	6060
Width (mm)	2440
Height (mm)	2600
* (electrical demand)	
** KVA Generator & Switch Gear (optional)	



**General note\*** : Allow between 250mm – 400mm added to the width for the control panel

**Structure** : Insulated structure, doors and ceiling: Polystyrene insulation sandwiched between white CHROMADEK® (0.6mm) faceplate both sides.

**Airflow** : Galvanised cased axial fans with high-speed Class H 3 phase (380v) motors and aluminium impellor and blades.

**Heating** : 750Lt Boiler

**Electric Panel** : Equipped with isolator, circuit breakers, fan contactor and overload, heater contactor, overheat safety thermostat, over/under voltage monitor, emergency stop, temperature controller and sensor, digital timer.